

BOGE Model	Max. pressure**		Receiver volume Litres	Effective free air delivery*		Motor power		Dimensions silenced	Dimensions super-silenced	Compressed air outlet	Weight silenced kg	Weight super-silenced. kg
	bar	psig		m <sup>3</sup> /min	cfm	kW	HP	W x D x H mm	W x D x H mm			
C 9 LF	8	115	–	0.26-1.27	9-45	7.5	10	1020 x 532 x 723	1020 x 532 x 796	G 1/2	200	208
C 9 LF	10	150	–	0.25-1.12	9-40	7.5	10	1020 x 532 x 723	1020 x 532 x 796	G 1/2	200	208
C 9 LF	13	190	–	0.24-0.93	8-33	7.5	10	1020 x 532 x 723	1020 x 532 x 796	G 1/2	200	208
C 9 LFR	8	115	270	0.26-1.27	9-45	7.5	10	1820 x 633 x 1270	1820 x 633 x 1343	G 1/2	315	323
C 9 LFR	10	150	270	0.25-1.12	9-40	7.5	10	1820 x 633 x 1270	1820 x 633 x 1343	G 1/2	315	323
C 9 LFR	13	190	250	0.24-0.93	8-33	7.5	10	1620 x 633 x 1270	1620 x 633 x 1343	G 1/2	310	318
C 9 LFDR	8	115	270	0.26-1.27	9-45	7.5	10	1820 x 633 x 1270	1820 x 633 x 1343	G 1/2	362	370
C 9 LFDR	10	150	270	0.25-1.12	9-40	7.5	10	1820 x 633 x 1270	1820 x 633 x 1343	G 1/2	362	370
C 9 LFDR	13	190	250	0.24-0.93	8-33	7.5	10	1620 x 633 x 1270	1620 x 633 x 1343	G 1/2	357	365

\* Free air delivery figures in accordance with ISO 1217, Appendix E, at 20°C ambient temperature and maximum pressure. Emitted sound pressure levels from 72 dB(A) according to DIN EN ISO 2151:2009

\*\* Max. pressure of the compressor

Ask for further receiver dimensions.