

Compressor Units

BOGE Type	Receiver volume	Flow capacity (Displacement)		Flow capacity (FAD as VDMA 4362)		Compressor speed	Number of cylinders	Motor		Dimensions W x D x H	Weight
	Litres	L/min	cfm	L/min	cfm			min ⁻¹	kW		
10 bar / 150 psig Standard											
SB 270/ 150		270	9.5	185	6.5	650	1	1.5	2.0	1540x480x1030	160
SB 370/ 150		370	13.0	260	9.0	900	1	2.2	3.0	1540x480x1030	160
SB 475/ 150		475	17.0	340	12.0	1150	1	3.0	4.0	1640x570x1160	210
SB 710/ 350		710	25	542	20	730	2	4.0	5.0	1930x740x1470	305
SB 970/ 350		970	35	734	26	1010	2	5.5	7.5	1930x740x1470	325
SB 1330/ 500		1330	47	1009	36	920	3	7.5	10.0	1920x740x1530	380
SB 2030/ 750		2030	72	1508	54	1050	4	11.0	15.0	2000x750x1720	510
SB 2600/ 750		2600	92	1913	68	1350	4	15.0	20.0	2000x750x1720	520

Compressor Units

BOGE Type	Receiver volume	Flow capacity (Displacement)		Flow capacity (FAD as VDMA 4362)		Compressor speed	Number of cylinders	Motor		Dimensions W x D x H	Weight
	Litres	L/min	cfm	L/min	cfm			min ⁻¹	kW		
15 bar / 220 psig Standard											
SBM 320/ 350		320	12	283	10	650	2	2.2	3.0	1720x700x1440	280
SBM 450/ 350		450	16	394	14	920	2	3.0	4.0	1720x700x1440	295
SBM 610/ 350		610	22	541	19	625	3	4.0	5.0	1930x740x1470	360
SBM 800/ 500		800	29	693	25	830	3	5.5	7.5	1920x740x1530	435
SBM 1100/ 500		1100	39	928	33	1130	3	7.5	10.0	1920x740x1530	445
SBM 1640/ 500		1640	58	1319	47	1130	4	11.0	15.0	2000x870x1720	575
SBM 2030/ 500		2030	72	1615	58	1400	4	15.0	20.0	2000x870x1720	525