

BOGE Model	Max. pressure		Effective free air delivery*		Motor power		Dimensions W x D x H mm	Compressed air outlet	Weight kg
	bar	psig	m ³ /min	cfm	kW	HP			
C 15	8	115	1.74	61	11.0	15	772 x 1056 x 1735	G 1	410
C 15	10	150	1.53	54	11.0	15	772 x 1056 x 1735	G 1	410
C 15	13	190	1.33	22	11.0	15	772 x 1056 x 1735	G 1	410
C 16	8	115	1.89	66	11.0	15	772 x 1056 x 1735	G 1	432
C 16	10	150	1.63	57	11.0	15	772 x 1056 x 1735	G 1	432
C 16	13	190	1.35	47	11.0	15	772 x 1056 x 1735	G 1	432
C 20	8	115	2.55	90	15.0	20	772 x 1056 x 1735	G 1	438
C 20	10	150	2.25	79	15.0	20	772 x 1056 x 1735	G 1	438
C 20	13	190	1.89	66	15.0	20	772 x 1056 x 1735	G 1	438
C 25	8	115	3.10	109	18.5	25	772 x 1056 x 1735	G 1	499
C 25	10	150	2.71	95	18.5	25	772 x 1056 x 1735	G 1	499
C 25	13	190	2.32	81	18.5	25	772 x 1056 x 1735	G 1	499
C 30	8	115	3.62	127	22.0	30	772 x 1056 x 1735	G 1	461
C 30	10	150	3.21	113	22.0	30	772 x 1056 x 1735	G 1	461
C 30	13	190	2.71	95	22.0	30	772 x 1056 x 1735	G 1	461

* Free air delivery for the complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound pressure values from 63 dB(A) according to DIN EN ISO 2151:2009

BOGE Model	Max. pressure**		Effective free air delivery*		Motor power		Dimensions W x D x H mm	Compressed air outlet	Weight kg
	bar	psig	m ³ /min	cfm	kW	HP			
C 15 D	8	115	1.74	61	11.0	15	1072 x 1056 x 1735	G 1	510
C 15 D	10	150	1.53	54	11.0	15	1072 x 1056 x 1735	G 1	510
C 15 D	13	190	1.33	22	11.0	15	1072 x 1056 x 1735	G 1	510
C 16 D	8	115	1.89	66	11.0	15	1072 x 1056 x 1735	G 1	532
C 16 D	10	150	1.63	57	11.0	15	1072 x 1056 x 1735	G 1	532
C 16 D	13	190	1.35	47	11.0	15	1072 x 1056 x 1735	G 1	532
C 20 D	8	115	2.55	90	15.0	20	1072 x 1056 x 1735	G 1	538
C 20 D	10	150	2.25	79	15.0	20	1072 x 1056 x 1735	G 1	538
C 20 D	13	190	1.89	66	15.0	20	1072 x 1056 x 1735	G 1	538
C 25 D	8	115	3.10	109	18.5	25	1072 x 1056 x 1735	G 1	599
C 25 D	10	150	2.71	95	18.5	25	1072 x 1056 x 1735	G 1	599
C 25 D	13	190	2.32	81	18.5	25	1072 x 1056 x 1735	G 1	599
C 30 D	8	115	3.62	127	22.0	30	1072 x 1056 x 1735	G 1	561
C 30 D	10	150	3.21	113	22.0	30	1072 x 1056 x 1735	G 1	561
C 30 D	13	190	2.71	95	22.0	30	1072 x 1056 x 1735	G 1	561

* Free air delivery for the complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound pressure values from 63 dB(A) according to DIN EN ISO 2151:2009

** Max. pressure of the compressor