

BOGE Model	Max. pressure		Effective free air delivery*		Motor power				Dimensions ¹⁾	Dimensions ²⁾	Compressed air outlet	Weight silenced	Weight super-silenced
	bar	psig	m ³ /min	cfm	Main drive motor		Fan motor		W x D x H mm	W x D x H mm		kg	kg
					kW	HP	kW	HP					
S 151	8	115	19.40	685	110	150	4.00	5.50	2265x1585x2005	2565x1585x2505	DN 80	3100	3200
S 151	10	150	17.00	600	110	150	4.00	5.50	2265x1585x2005	2565x1585x2505	DN 80	3100	3200
S 151	13	190	14.40	508	110	150	4.00	5.50	2265x1585x2005	2565x1585x2505	DN 80	3100	3200
S 180	8	115	23.30	825	132	180	4.00	5.50	2265x1585x2005	2565x1585x2505	DN 80	3400	3500
S 180	10	150	20.80	735	132	180	4.00	5.50	2265x1585x2005	2565x1585x2505	DN 80	3400	3500
S 180	13	190	17.80	630	132	180	4.00	5.50	2265x1585x2005	2565x1585x2505	DN 80	3400	3500
S 220	8	115	27.90	990	160	220	4.00	5.50	2265x1585x2005	2565x1585x2505	DN 80	3400	3500
S 220	10	150	25.10	890	160	220	4.00	5.50	2265x1585x2005	2565x1585x2505	DN 80	3400	3500
S 220	13	190	21.70	770	160	220	4.00	5.50	2265x1585x2005	2565x1585x2505	DN 80	3400	3500
S 271	8	115	34.70	1225	200	270	5.50	7.50	3100x1910x2145	3500x1910x2645	DN 100	4500	4600
S 271	10	150	30.50	1077	200	270	5.50	7.50	3100x1910x2145	3500x1910x2645	DN 100	4500	4600
S 271	13	190	24.70	872	200	270	5.50	7.50	3100x1910x2145	3500x1910x2645	DN 100	4500	4600
S 341	8	115	40.80	1441	250	340	7.50	10.00	3100x1910x2145	3500x1910x2645	DN 100	5000	5100
S 341	10	150	37.10	1310	250	340	7.50	10.00	3100x1910x2145	3500x1910x2645	DN 100	5000	5100
S 341	13	190	31.70	1119	250	340	7.50	10.00	3100x1910x2145	3500x1910x2645	DN 100	5000	5100

* Free air delivery for the complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound pressure values from 68 dB(A) according to DIN EN ISO 2151:2009

¹⁾ Super-silenced at the intake end

²⁾ Super-silenced at the intake end and discharge end