

Compressor Units

BOGE Type	Flow capacity (Displacement)		Flow capacity (FAD as VDMA 4362)		Com- pressor speed min ⁻¹	Number of cylinders	Motor		Dimensions W x D x H approx. mm	Weight approx. kg
	L/min	cfm	L/min	cfm			kW	HP		
10 bar Super-silenced										
SC 6	710	25	542	20	730	2	4	5.5	830x1120x1570	341
SC 8	970	35	734	26	1010	2	5.5	7.5	830x1120x1570	363
SC 10	1330	47	1009	36	920	3	7.5	10	830x1120x1570	389
SC 15	2030	72	1508	54	1050	4	11	15	830x1120x1570	453
SC 20	2600	92	1913	68	1350	4	15	20	830x1120x1570	463
15 bar Super-silenced										
SC 3	320	12	283	10	650	2	2.2	3	830x1120x1570	337
SC 4	450	16	394	14	920	2	3	4	830x1120x1570	343
SC 6	610	22	541	19	625	3	4	5.5	830x1120x1570	368
SC 8	800	29	693	25	830	3	5.5	7.5	830x1120x1570	390
SC 10	1100	39	928	33	1130	3	7.5	10	830x1120x1570	397
SC 15	1640	58	1319	47	1130	4	11	15	830x1120x1570	463
SC 20	2030	72	1615	58	1400	4	15	20	830x1120x1570	473

Sound pressure level according to PN8NTC2.3 from **60 dB(A)**