

SRD/SBD 125 and 250 Series

Compressor Systems

BOGE Type	Flow capacity (Displacement)			Compressor speed min ⁻¹	Number of cylinders	Motor		Dimensions W x D x H mm	Compressed air outlet	Weight kg
	L/min	m ³ /h	cfm			kW	HP			
10 bar / 150 psig Standard										
SRD 125	125	7.5	4.5	1450	1	0.75	1	470x275x340	DN 12	32
SRD 250	250	15.0	9	1450	2	1.5	2.0	485x345x335	DN 12	38
10 bar / 150 psig Super-silenced										
SRDL 125	125	7.5	4.5	1450	1	0.75	1	600x400x475	DN 12	61
SRDL 250	250	15.0	9	1450	2	1.5	2.0	600x400x475	DN 12	67

Compressor System, for intermittent operation

15 bar / 220 psig Standard										
SRMD 125	125	7.5	4.5	1450	1	0.75	1	470x275x340	DN 12	32
SRMD 250	250	15.0	9	1450	2	1.5	2.0	485x345x335	DN 12	38

Compressor Units

BOGE Type	Receiver volume Litres	Flow capacity (Displacement)			Compressor speed min ⁻¹	Number of cylinders	Motor		Dimensions W x D x H mm	Compressed air outlet	Weight kg
		L/min	m ³ /h	cfm			kW	HP			
10 bar / 150 psig Standard											
SBD 125/18	125	7.5	4.5	1450	1	0.75	1	530x300x645	G 1/4	42	
SBD 250/18	250	15.0	9	1450	2	1.5	2.0	525x300x650	G 1/4	51	
10 bar / 150 psig Super-silenced											
SBDL 125/50	125	7.5	4.5	1450	1	0.75	1	1025x405x875	G 3/8	74	
SBDL 250/50	250	15.0	9	1450	2	1.5	2.0	1025x405x875	G 3/8	84	

Compressor Units, for intermittent operation

15 bar / 220 psig Standard											
SBMD 125/50	125	7.5	4.5	1450	1	0.75	1	850x350x720	G 3/8	54	
SBMD 250/50	250	15.0	9	1450	2	1.5	2.0	850x350x705	G 3/8	63	

Compressor Duplex Packages

BOGE Type	Receiver volume Litres	Flow capacity (Displacement)			Compressor speed min ⁻¹	Number of cylinders	Motor		Dimensions W x D x H mm	Compressed air outlet	Weight kg
		L/min	m ³ /h	cfm			kW	HP			
10 bar / 150 psig Standard											
SBD 125/150 D	2 x 125	2 x 7.5	2 x 4.5	1450	2 x 1	2 x 0.75	2 x 1	1450x550x840	G 1/2	140	
SBD 250/150 D	2 x 250	2 x 15.0	2 x 9	1450	2 x 2	2 x 1.5	2 x 2.0	1450x550x845	G 1/2	157	
10 bar / 150 psig Super-silenced											
SBDL 125/150 D	2 x 125	2 x 7.5	2 x 4.5	1450	2 x 1	2 x 0.75	2 x 1	1585x520x980	G 1/2	195	
SBDL 250/150 D	2 x 250	2 x 15.0	2 x 9	1450	2 x 2	2 x 1.5	2 x 2.0	1585x520x980	G 1/2	210	